



KONICA MINOLTA

Voluntary Product Accessibility Template

Compliance Status

Laser Printer

7/07/05



PagePro 1250E

SECTION 1194.25. SELF CONTAINED, CLOSED PRODUCTS DETAIL VOLUNTARY PRODUCT ACCESSIBILITY TEMPLATE (VPAT)

CRITERIA	SUPPORTING FEATURES	REMARKS AND EXPLANATIONS
(a) Self contained products shall be usable by people with disabilities without requiring an end-user to attach Assistive Technology to the product. Personal headsets for private listening are not Assistive Technology.	Monochrome Laser Printer; up to 17 ppm; 1200 x 1200 dpi resolution; memory 16 mb (standard), up to 144 mb (max); The printer can be operated with one hand.	No Assistive Technology is required to use this Printer;
(b) When a timed response is required, the user shall be alerted and given sufficient time to indicate more time is required.	Any timed response associated with this printer provides at least two (2) minutes for the user to respond	Any timed response features associated with this printer give the user sufficient time to respond
(c) Where a product utilizes touchscreens or contact-sensitive controls, an input method shall be provided that complies with §1194.23 (k) (1) through (4).	This product does not utilize a touchscreen and any contact sensitive controls comply with § 1194.23 (k)(1) through (4)	This product does not utilize a touch screen
(d) When biometric forms of user identification or control are used, an alternative form of identification or activation, which does not require the user to possess particular biological characteristics, shall also be provided.	Not applicable	This product does not utilize biometric controls
(e) When products provide auditory output, the audio signal shall be provided at a standard signal level through an industry standard connector that will allow for private listening. The product must provide the ability to interrupt, pause, and restart the audio at anytime.	Not applicable - This product does not provide auditory output as a standard feature. However, there is a Buzzbox™ available as an option that provides auditory and/or visual notification of any printer offline condition. Users with the Buzzbox™ can select a flashing light and/or beeping indicator to notify that the printer requires attention.	This product does not provide auditory output as a standard feature
(f) When products deliver voice output in a public area, incremental volume control shall be provided with output amplification up to a level of at least 65 dB. Where the ambient noise level of the environment is above 45 dB, a volume gain of at least 20 dB above the ambient level shall be user selectable. A function shall be provided to automatically reset the volume to the default level after every use.	Not applicable	This product does not require or deliver voice output in a public area



(g) Color coding shall not be used as the only means of conveying information, indicating an action, prompting a response, or distinguishing a visual element.	This product uses text labels, symbols and/or icons to convey information	Color coding is not used as the sole means of conveying information on this printer
(h) When a product permits a user to adjust color and contrast settings, a range of color selections capable of producing a variety of contrast levels shall be provided.	Not applicable	This product does not permit a user to adjust the color or contrast setting on the LCD panel.
(i) Products shall be designed to avoid causing the screen to flicker with a frequency greater than 2 Hz and lower than 55 Hz.	Not applicable	This product does not have any screens that flicker or flash.
(j) (1) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: The position of any operable control shall be determined with respect to a vertical plane, which is 48 inches in length, centered on the operable control, and at the maximum protrusion of the product within the 48 inch length on products which are freestanding, non-portable, and intended to be used in one location and which have operable controls.	All operable controls on this Product are located within 24 inches of the front of the printer. There are indicator lights on the front panel of the printer which are visible from across the room.	This product is portable and may be easily moved from one location to another
(j)(2) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is 10 inches or less behind the reference plane, the height shall be 54 inches maximum and 15 inches minimum above the floor.	The operator panel on this Printer is on the front of the product and can be identified by touch. The printer is portable and can be placed at the convenience of the user. KMPS offers optional ADA-compliant printer stands which are designed to provide easier access for physically challenged users.	This product is portable and may be easily moved from one location to another for the convenience of the user.
(j)(3) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is more than 10 inches and not more than 24 inches behind the reference plane, the height shall be 46 inches maximum and 15 inches minimum above the floor.	The operator panel on this Printer is on the front of the product and can be identified by touch. All operable controls are located within 24 inches of the front of the printer. The printer is portable and can be placed at the convenience of the user.	This product is portable and may be easily moved from one location to another for the convenience of the user.
(j)(4) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Operable controls shall not be more than 24 inches behind the reference plane.	The operator panel on this Printer is on the front of the product and can be identified by touch. All operable controls are located within 24 inches of the front of the printer. The printer is portable and can be placed at the convenience of the user.	This product is portable and may be easily moved from one location to another for the convenience of the user.

**PagePro 1350W**SECTION 1194.25. SELF CONTAINED, CLOSED PRODUCTS
DETAIL VOLUNTARY PRODUCT ACCESSIBILITY TEMPLATE (VPAT)

CRITERIA	SUPPORTING FEATURES	REMARKS AND EXPLANATIONS
(a) Self contained products shall be usable by people with disabilities without requiring an end-user to attach Assistive Technology to the product. Personal headsets for private listening are not Assistive Technology.	Monochrome Laser Printer; 21 ppm; 1200 x 1200 dpi resolution; memory 8 mb; The printer can be operated with one hand.	No Assistive Technology is required to use this Printer;
(b) When a timed response is required, the user shall be alerted and given sufficient time to indicate more time is required.	Any timed response associated with this printer provides at least two (2) minutes for the user to respond	Any timed response features associated with this printer give the user sufficient time to respond
(c) Where a product utilizes touchscreens or contact-sensitive controls, an input method shall be provided that complies with §1194.23 (k) (1) through (4).	This product does not utilize a touchscreen and any contact sensitive controls comply with § 1194.23 (k)(1) through (4)	This product does not utilize a touchscreen
(d) When biometric forms of user identification or control are used, an alternative form of identification or activation, which does not require the user to possess particular biological characteristics, shall also be provided.	Not applicable	This product does not utilize biometric controls
(e) When products provide auditory output, the audio signal shall be provided at a standard signal level through an industry standard connector that will allow for private listening. The product must provide the ability to interrupt, pause, and restart the audio at anytime.	Not applicable - This product does not provide auditory output as a standard or optional feature.	This product does not provide auditory output as a standard feature
(f) When products deliver voice output in a public area, incremental volume control shall be provided with output amplification up to a level of at least 65 dB. Where the ambient noise level of the environment is above 45 dB, a volume gain of at least 20 dB above the ambient level shall be user selectable. A function shall be provided to automatically reset the volume to the default level after every use.	Not applicable	This product does not require or deliver voice output in a public area
(g) Color coding shall not be used as the only means of conveying information, indicating an action, prompting a response, or distinguishing a visual element.	This product uses text labels, symbols and/or icons to convey information	Color coding is not used as the sole means of conveying information on this printer



(h) When a product permits a user to adjust color and contrast settings, a range of color selections capable of producing a variety of contrast levels shall be provided.	Not applicable	This product does not permit a user to adjust the color or contrast setting on the LCD panel.
(i) Products shall be designed to avoid causing the screen to flicker with a frequency greater than 2 Hz and lower than 55 Hz.	Not applicable	This product does not have any screens that flicker or flash.
(j) (1) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: The position of any operable control shall be determined with respect to a vertical plane, which is 48 inches in length, centered on the operable control, and at the maximum protrusion of the product within the 48 inch length on products which are freestanding, non-portable, and intended to be used in one location and which have operable controls.	All operable controls on this Product are located within 24 inches of the front of the printer. There are indicator lights on the front panel of the printer which are visible from across the room.	This product is portable and may be easily moved from one location to another
(j)(2) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is 10 inches or less behind the reference plane, the height shall be 54 inches maximum and 15 inches minimum above the floor.	The operator panel on this Printer is on the front of the product and can be identified by touch. The printer is portable and can be placed at the convenience of the user. KMPS offers optional ADA-compliant printer stands which are designed to provide easier access for physically challenged users.	This product is portable and may be easily moved from one location to another for the convenience of the user.
(j)(3) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is more than 10 inches and not more than 24 inches behind the reference plane, the height shall be 46 inches maximum and 15 inches minimum above the floor.	The operator panel on this Printer is on the front of the product and can be identified by touch. All operable controls are located within 24 inches of the front of the printer. The printer is portable and can be placed at the convenience of the user.	This product is portable and may be easily moved from one location to another for the convenience of the user.
(j)(4) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Operable controls shall not be more than 24 inches behind the reference plane.	The operator panel on this Printer is on the front of the product and can be identified by touch. All operable controls are located within 24 inches of the front of the printer. The printer is portable and can be placed at the convenience of the user.	This product is portable and may be easily moved from one location to another for the convenience of the user.

**PagePro 9100**SECTION 1194.25. SELF CONTAINED, CLOSED PRODUCTS
DETAIL VOLUNTARY PRODUCT ACCESSIBILITY TEMPLATE (VPAT)

CRITERIA	SUPPORTING FEATURES	REMARKS AND EXPLANATIONS
(a) Self contained products shall be usable by people with disabilities without requiring an end-user to attach Assistive Technology to the product. Personal headsets for private listening are not Assistive Technology.	Monochrome Laser Printer; up to 35 ppm; 1200 x 1200 dpi resolution; memory 64 mb (standard) /512 mb (Max); The printer can be operated with one hand.	No Assistive Technology is required to use this Printer;
(b) When a timed response is required, the user shall be alerted and given sufficient time to indicate more time is required.	Any timed response associated with this printer provides at least two (2) minutes for the user to respond	Any timed response features associated with this printer give the user sufficient time to respond
(c) Where a product utilizes touchscreens or contact-sensitive controls, an input method shall be provided that complies with §1194.23 (k) (1) through (4).	This product does not utilize a touchscreen and any contact sensitive controls comply with § 1194.23 (k)(1) through (4)	This product does not utilize a touchscreen
(d) When biometric forms of user identification or control are used, an alternative form of identification or activation, which does not require the user to possess particular biological characteristics, shall also be provided.	Not applicable	This product does not utilize biometric controls
(e) When products provide auditory output, the audio signal shall be provided at a standard signal level through an industry standard connector that will allow for private listening. The product must provide the ability to interrupt, pause, and restart the audio at anytime.	Not applicable - This product does not provide auditory output as a standard feature. However, there is a Buzzbox™ available as an option that provides auditory and/or visual notification of any printer offline condition. Users with the Buzzbox™ can select a flashing light and/or beeping indicator to notify that the printer requires attention.	This product does not provide auditory output as a standard feature
(f) When products deliver voice output in a public area, incremental volume control shall be provided with output amplification up to a level of at least 65 dB. Where the ambient noise level of the environment is above 45 dB, a volume gain of at least 20 dB above the ambient level shall be user selectable. A function shall be provided to automatically reset the volume to the default level after every use.	Not applicable	This product does not require or deliver voice output in a public area



(g) Color coding shall not be used as the only means of conveying information, indicating an action, prompting a response, or distinguishing a visual element.	This product uses text labels, symbols and/or icons to convey information	Color coding is not used as the sole means of conveying information on this printer
(h) When a product permits a user to adjust color and contrast settings, a range of color selections capable of producing a variety of contrast levels shall be provided.	Not applicable	This product does not permit a user to adjust the color or contrast setting on the LCD panel.
(i) Products shall be designed to avoid causing the screen to flicker with a frequency greater than 2 Hz and lower than 55 Hz.	Not applicable	This product does not have any screens that flicker or flash.
(j) (1) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: The position of any operable control shall be determined with respect to a vertical plane, which is 48 inches in length, centered on the operable control, and at the maximum protrusion of the product within the 48 inch length on products which are freestanding, non-portable, and intended to be used in one location and which have operable controls.	All operable controls on this Product are located within 24 inches of the front of the printer. There are indicator lights on the front panel of the printer which are visible from across the room.	This product is portable and may be easily moved from one location to another
(j)(2) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is 10 inches or less behind the reference plane, the height shall be 54 inches maximum and 15 inches minimum above the floor.	The operator panel on this Printer is on the front of the product and can be identified by touch. The printer is portable and can be placed at the convenience of the user. KMPS offers optional ADA-compliant printer stands which are designed to provide easier access for physically challenged users.	This product is portable and may be easily moved from one location to another for the convenience of the user.
(j)(3) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is more than 10 inches and not more than 24 inches behind the reference plane, the height shall be 46 inches maximum and 15 inches minimum above the floor.	The operator panel on this Printer is on the front of the product and can be identified by touch. All operable controls are located within 24 inches of the front of the printer. The printer is portable and can be placed at the convenience of the user.	This product is portable and may be easily moved from one location to another for the convenience of the user.
(j)(4) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Operable controls shall not be more than 24 inches behind the reference plane.	The operator panel on this Printer is on the front of the product and can be identified by touch. All operable controls are located within 24 inches of the front of the printer. The printer is portable and can be placed at the convenience of the user.	This product is portable and may be easily moved from one location to another for the convenience of the user.



magicolor 2300W

**SECTION 1194.25. SELF CONTAINED, CLOSED PRODUCTS
DETAIL VOLUNTARY PRODUCT ACCESSIBILITY TEMPLATE (VPAT)**

CRITERIA	SUPPORTING FEATURES	REMARKS AND EXPLANATIONS
(a) Self contained products shall be usable by people with disabilities without requiring an end-user to attach Assistive Technology to the product. Personal headsets for private listening are not Assistive Technology.	Color laser printer; up to 16 ppm monochrome and up to 4 ppm color; 1200 x 600 dpi resolution; memory 32 mb (standard)/288 mb (Max); The printer can be operated with one hand.	No Assistive Technology is required to use this Printer;
(b) When a timed response is required, the user shall be alerted and given sufficient time to indicate more time is required.	Any timed response associated with this printer provides at least two (2) minutes for the user to respond	Any timed response features associated with this printer give the user sufficient time to respond
(c) Where a product utilizes touchscreens or contact-sensitive controls, an input method shall be provided that complies with §1194.23 (k) (1) through (4).	This product does not utilize a touchscreen and any contact sensitive controls comply with § 1194.23 (k)(1) through (4)	This product does not utilize a touchscreen
(d) When biometric forms of user identification or control are used, an alternative form of identification or activation, which does not require the user to possess particular biological characteristics, shall also be provided.	Not applicable	This product does not utilize biometric controls
(e) When products provide auditory output, the audio signal shall be provided at a standard signal level through an industry standard connector that will allow for private listening. The product must provide the ability to interrupt, pause, and restart the audio at anytime.	Not applicable - This product does not provide auditory output as a standard or optional feature.	This product does not provide auditory output as a standard feature
(f) When products deliver voice output in a public area, incremental volume control shall be provided with output amplification up to a level of at least 65 dB. Where the ambient noise level of the environment is above 45 dB, a volume gain of at least 20 dB above the ambient level shall be user selectable. A function shall be provided to automatically reset the volume to the default level after every use.	Not applicable	This product does not require or deliver voice output in a public area
(g) Color coding shall not be used as the only means of conveying information, indicating an action, prompting a response, or distinguishing a visual element.	This product uses text labels, symbols and/or icons to convey information	Color coding is not used as the sole means of conveying information on this printer



(h) When a product permits a user to adjust color and contrast settings, a range of color selections capable of producing a variety of contrast levels shall be provided.	Not applicable	This product does not permit a user to adjust the color or contrast setting on the LCD panel.
(i) Products shall be designed to avoid causing the screen to flicker with a frequency greater than 2 Hz and lower than 55 Hz.	Not applicable	This product does not have any screens that flicker or flash.
(j) (1) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: The position of any operable control shall be determined with respect to a vertical plane, which is 48 inches in length, centered on the operable control, and at the maximum protrusion of the product within the 48 inch length on products which are freestanding, non-portable, and intended to be used in one location and which have operable controls.	All operable controls on this Product are located within 24 inches of the front of the printer. There are indicator lights on the front panel of the printer which are visible from across the room.	This product is portable and may be easily moved from one location to another
(j)(2) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is 10 inches or less behind the reference plane, the height shall be 54 inches maximum and 15 inches minimum above the floor.	The operator panel on this Printer is on the front of the product and can be identified by touch. The printer is portable and can be placed at the convenience of the user. KMPS offers optional ADA-compliant printer stands which are designed to provide easier access for physically challenged users.	This product is portable and may be easily moved from one location to another for the convenience of the user.
(j)(3) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is more than 10 inches and not more than 24 inches behind the reference plane, the height shall be 46 inches maximum and 15 inches minimum above the floor.	The operator panel on this Printer is on the front of the product and can be identified by touch. All operable controls are located within 24 inches of the front of the printer. The printer is portable and can be placed at the convenience of the user.	This product is portable and may be easily moved from one location to another for the convenience of the user.
(j)(4) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Operable controls shall not be more than 24 inches behind the reference plane.	The operator panel on this Printer is on the front of the product and can be identified by touch. All operable controls are located within 24 inches of the front of the printer. The printer is portable and can be placed at the convenience of the user.	This product is portable and may be easily moved from one location to another for the convenience of the user.



magicolor 2300DL

**SECTION 1194.25. SELF CONTAINED, CLOSED PRODUCTS
DETAIL VOLUNTARY PRODUCT ACCESSIBILITY TEMPLATE (VPAT)**

CRITERIA	SUPPORTING FEATURES	REMARKS AND EXPLANATIONS
(a) Self contained products shall be usable by people with disabilities without requiring an end-user to attach Assistive Technology to the product. Personal headsets for private listening are not Assistive Technology.	Color laser printer; up to 16 ppm monochrome and up to 4 ppm color; 2400 x 600 dpi resolution; memory 32 mb (standard)/288 mb (Max); The printer can be operated with one hand.	No Assistive Technology is required to use this Printer;
(b) When a timed response is required, the user shall be alerted and given sufficient time to indicate more time is required.	Any timed response associated with this printer provides at least two (2) minutes for the user to respond	Any timed response features associated with this printer give the user sufficient time to respond
(c) Where a product utilizes touchscreens or contact-sensitive controls, an input method shall be provided that complies with §1194.23 (k) (1) through (4).	This product does not utilize a touchscreen and any contact sensitive controls comply with § 1194.23 (k)(1) through (4)	This product does not utilize a touchscreen
(d) When biometric forms of user identification or control are used, an alternative form of identification or activation, which does not require the user to possess particular biological characteristics, shall also be provided.	Not applicable	This product does not utilize biometric controls
(e) When products provide auditory output, the audio signal shall be provided at a standard signal level through an industry standard connector that will allow for private listening. The product must provide the ability to interrupt, pause, and restart the audio at anytime.	Not applicable - This product does not provide auditory output as a standard or optional feature.	This product does not provide auditory output as a standard feature
(f) When products deliver voice output in a public area, incremental volume control shall be provided with output amplification up to a level of at least 65 dB. Where the ambient noise level of the environment is above 45 dB, a volume gain of at least 20 dB above the ambient level shall be user selectable. A function shall be provided to automatically reset the volume to the default level after every use.	Not applicable	This product does not require or deliver voice output in a public area
(g) Color coding shall not be used as the only means of conveying information, indicating an action, prompting a response, or distinguishing a visual element.	This product uses text labels, symbols and/or icons to convey information	Color coding is not used as the sole means of conveying information on this printer



(h) When a product permits a user to adjust color and contrast settings, a range of color selections capable of producing a variety of contrast levels shall be provided.	Not applicable	This product does not permit a user to adjust the color or contrast setting on the LCD panel.
(i) Products shall be designed to avoid causing the screen to flicker with a frequency greater than 2 Hz and lower than 55 Hz.	Not applicable	This product does not have any screens that flicker or flash.
(j) (1) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: The position of any operable control shall be determined with respect to a vertical plane, which is 48 inches in length, centered on the operable control, and at the maximum protrusion of the product within the 48 inch length on products which are freestanding, non-portable, and intended to be used in one location and which have operable controls.	All operable controls on this Product are located within 24 inches of the front of the printer. There are indicator lights on the front panel of the printer which are visible from across the room.	This product is portable and may be easily moved from one location to another
(j)(2) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is 10 inches or less behind the reference plane, the height shall be 54 inches maximum and 15 inches minimum above the floor.	The operator panel on this Printer is on the front of the product and can be identified by touch. The printer is portable and can be placed at the convenience of the user. KMPS offers optional ADA-compliant printer stands which are designed to provide easier access for physically challenged users.	This product is portable and may be easily moved from one location to another for the convenience of the user.
(j)(3) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is more than 10 inches and not more than 24 inches behind the reference plane, the height shall be 46 inches maximum and 15 inches minimum above the floor.	The operator panel on this Printer is on the front of the product and can be identified by touch. All operable controls are located within 24 inches of the front of the printer. The printer is portable and can be placed at the convenience of the user.	This product is portable and may be easily moved from one location to another for the convenience of the user.
(j)(4) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Operable controls shall not be more than 24 inches behind the reference plane.	The operator panel on this Printer is on the front of the product and can be identified by touch. All operable controls are located within 24 inches of the front of the printer. The printer is portable and can be placed at the convenience of the user.	This product is portable and may be easily moved from one location to another for the convenience of the user.



magicolor 2350

**SECTION 1194.25. SELF CONTAINED, CLOSED PRODUCTS
DETAIL VOLUNTARY PRODUCT ACCESSIBILITY TEMPLATE (VPAT)**

CRITERIA	SUPPORTING FEATURES	REMARKS AND EXPLANATIONS
(a) Self contained products shall be usable by people with disabilities without requiring an end-user to attach Assistive Technology to the product. Personal headsets for private listening are not Assistive Technology.	Color laser printer; up to 18 ppm monochrome and up to 4 ppm color; 2400 x 600 dpi resolution; memory 32 mb (standard)/288 mb (Max); The printer can be operated with one hand.	No Assistive Technology is required to use this Printer;
(b) When a timed response is required, the user shall be alerted and given sufficient time to indicate more time is required.	Any timed response associated with this printer provides at least two (2) minutes for the user to respond	Any timed response features associated with this printer give the user sufficient time to respond
(c) Where a product utilizes touchscreens or contact-sensitive controls, an input method shall be provided that complies with §1194.23 (k) (1) through (4).	This product does not utilize a touchscreen and any contact sensitive controls comply with § 1194.23 (k)(1) through (4)	This product does not utilize a touchscreen
(d) When biometric forms of user identification or control are used, an alternative form of identification or activation, which does not require the user to possess particular biological characteristics, shall also be provided.	Not applicable	This product does not utilize biometric controls
(e) When products provide auditory output, the audio signal shall be provided at a standard signal level through an industry standard connector that will allow for private listening. The product must provide the ability to interrupt, pause, and restart the audio at anytime.	Not applicable - This product does not provide auditory output as a standard feature. However, there is a Buzzbox™ available as an option that provides auditory and/or visual notification of any printer offline condition. Users with the Buzzbox™ can select a flashing light and/or beeping indicator to notify that the printer requires attention.	This product does not provide auditory output as a standard feature
(f) When products deliver voice output in a public area, incremental volume control shall be provided with output amplification up to a level of at least 65 dB. Where the ambient noise level of the environment is above 45 dB, a volume gain of at least 20 dB above the ambient level shall be user selectable. A function shall be provided to automatically reset the volume to the default level after every use.	Not applicable	This product does not require or deliver voice output in a public area



(g) Color coding shall not be used as the only means of conveying information, indicating an action, prompting a response, or distinguishing a visual element.	This product uses text labels, symbols and/or icons to convey information	Color coding is not used as the sole means of conveying information on this printer
(h) When a product permits a user to adjust color and contrast settings, a range of color selections capable of producing a variety of contrast levels shall be provided.	Not applicable	This product does not permit a user to adjust the color or contrast setting on the LCD panel.
(i) Products shall be designed to avoid causing the screen to flicker with a frequency greater than 2 Hz and lower than 55 Hz.	Not applicable	This product does not have any screens that flicker or flash.
(j) (1) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: The position of any operable control shall be determined with respect to a vertical plane, which is 48 inches in length, centered on the operable control, and at the maximum protrusion of the product within the 48 inch length on products which are freestanding, non-portable, and intended to be used in one location and which have operable controls.	All operable controls on this Product are located within 24 inches of the front of the printer. There are indicator lights on the front panel of the printer which are visible from across the room.	This product is portable and may be easily moved from one location to another
(j)(2) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is 10 inches or less behind the reference plane, the height shall be 54 inches maximum and 15 inches minimum above the floor.	The operator panel on this Printer is on the front of the product and can be identified by touch. The printer is portable and can be placed at the convenience of the user. KMPS offers optional ADA-compliant printer stands which are designed to provide easier access for physically challenged users.	This product is portable and may be easily moved from one location to another for the convenience of the user.
(j)(3) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is more than 10 inches and not more than 24 inches behind the reference plane, the height shall be 46 inches maximum and 15 inches minimum above the floor.	The operator panel on this Printer is on the front of the product and can be identified by touch. All operable controls are located within 24 inches of the front of the printer. The printer is portable and can be placed at the convenience of the user.	This product is portable and may be easily moved from one location to another for the convenience of the user.
(j)(4) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Operable controls shall not be more than 24 inches behind the reference plane.	The operator panel on this Printer is on the front of the product and can be identified by touch. All operable controls are located within 24 inches of the front of the printer. The printer is portable and can be placed at the convenience of the user.	This product is portable and may be easily moved from one location to another for the convenience of the user.



magicolor 2430 DL

**SECTION 1194.25. SELF CONTAINED, CLOSED PRODUCTS
DETAIL VOLUNTARY PRODUCT ACCESSIBILITY TEMPLATE**

CRITERIA	SUPPORTING FEATURES	REMARKS AND EXPLANATIONS
(a) Self contained products shall be usable by people with disabilities without requiring an end-user to attach Assistive Technology to the product. Personal headsets for private listening are not Assistive Technology.	Color laser printer; up to 20 ppm monochrome and up to 5 ppm color; 2400 x 600 dpi resolution; memory 32 mb (standard)/512 mb (Max); The printer can be operated with one hand.	No Assistive Technology is required to use this Printer;
(b) When a timed response is required, the user shall be alerted and given sufficient time to indicate more time is required.	Any timed response associated with this printer provides at least two (2) minutes for the user to respond	Any timed response features associated with this printer give the user sufficient time to respond
(c) Where a product utilizes touchscreens or contact-sensitive controls, an input method shall be provided that complies with §1194.23 (k) (1) through (4).	This product does not utilize a touchscreen and any contact sensitive controls comply with § 1194.23 (k)(1) through (4)	This product does not utilize a touchscreen
(d) When biometric forms of user identification or control are used, an alternative form of identification or activation, which does not require the user to possess particular biological characteristics, shall also be provided.	Not applicable	This product does not utilize biometric controls
(e) When products provide auditory output, the audio signal shall be provided at a standard signal level through an industry standard connector that will allow for private listening. The product must provide the ability to interrupt, pause, and restart the audio at anytime.	Not applicable - This product does not provide auditory output as a standard feature.	This product does not provide auditory output as a standard feature
(f) When products deliver voice output in a public area, incremental volume control shall be provided with output amplification up to a level of at least 65 dB. Where the ambient noise level of the environment is above 45 dB, a volume gain of at least 20 dB above the ambient level shall be user selectable. A function shall be provided to automatically reset the volume to the default level after every use.	Not applicable	This product does not require or deliver voice output in a public area
(g) Color coding shall not be used as the only means of conveying information, indicating an action, prompting a response, or distinguishing a visual element.	This product uses text labels, symbols and/or icons to convey information	Color coding is not used as the sole means of conveying information on this printer



(h) When a product permits a user to adjust color and contrast settings, a range of color selections capable of producing a variety of contrast levels shall be provided.	Not applicable	This product does not permit a user to adjust the color or contrast setting on the LCD panel.
(i) Products shall be designed to avoid causing the screen to flicker with a frequency greater than 2 Hz and lower than 55 Hz.	Not applicable	This product does not have any screens that flicker or flash.
(j) (1) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: The position of any operable control shall be determined with respect to a vertical plane, which is 48 inches in length, centered on the operable control, and at the maximum protrusion of the product within the 48 inch length on products which are freestanding, non-portable, and intended to be used in one location and which have operable controls.	All operable controls on this Product are located within 24 inches of the front of the printer. There are indicator lights on the front panel of the printer which are visible from across the room.	This product is portable and may be easily moved from one location to another
(j)(2) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is 10 inches or less behind the reference plane, the height shall be 54 inches maximum and 15 inches minimum above the floor.	The operator panel on this Printer is on the front of the product and can be identified by touch. The printer is portable and can be placed at the convenience of the user. KMPS offers optional ADA-compliant printer stands which are designed to provide easier access for physically challenged users.	This product is portable and may be easily moved from one location to another for the convenience of the user.
(j)(3) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is more than 10 inches and not more than 24 inches behind the reference plane, the height shall be 46 inches maximum and 15 inches minimum above the floor.	The operator panel on this Printer is on the front of the product and can be identified by touch. All operable controls are located within 24 inches of the front of the printer. The printer is portable and can be placed at the convenience of the user.	This product is portable and may be easily moved from one location to another for the convenience of the user.
(j)(4) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Operable controls shall not be more than 24 inches behind the reference plane.	The operator panel on this Printer is on the front of the product and can be identified by touch. All operable controls are located within 24 inches of the front of the printer. The printer is portable and can be placed at the convenience of the user.	This product is portable and may be easily moved from one location to another for the convenience of the user.



magicolor 2450

**SECTION 1194.25. SELF CONTAINED, CLOSED PRODUCTS
DETAIL VOLUNTARY PRODUCT ACCESSIBILITY TEMPLATE**

CRITERIA	SUPPORTING FEATURES	REMARKS AND EXPLANATIONS
(a) Self contained products shall be usable by people with disabilities without requiring an end-user to attach Assistive Technology to the product. Personal headsets for private listening are not Assistive Technology.	Color laser printer; up to 20 ppm monochrome and up to 5 ppm color; 600 x 600 dpi resolution; memory 128 mb(Standard) 128 mb (Option) 256 mb(Option) 512 mb (Option); The printer can be operated with one hand.	No Assistive Technology is required to use this Printer;
(b) When a timed response is required, the user shall be alerted and given sufficient time to indicate more time is required.	Any timed response associated with this printer provides at least two (2) minutes for the user to respond	Any timed response features associated with this printer give the user sufficient time to respond
(c) Where a product utilizes touchscreens or contact-sensitive controls, an input method shall be provided that complies with §1194.23 (k) (1) through (4).	This product does not utilize a touchscreen and any contact sensitive controls comply with § 1194.23 (k)(1) through (4)	This product does not utilize a touchscreen
(d) When biometric forms of user identification or control are used, an alternative form of identification or activation, which does not require the user to possess particular biological characteristics, shall also be provided.	Not applicable	This product does not utilize biometric controls
(e) When products provide auditory output, the audio signal shall be provided at a standard signal level through an industry standard connector that will allow for private listening. The product must provide the ability to interrupt, pause, and restart the audio at anytime.	Not applicable - This product does not provide auditory output as a standard feature.	This product does not provide auditory output as a standard feature
(f) When products deliver voice output in a public area, incremental volume control shall be provided with output amplification up to a level of at least 65 dB. Where the ambient noise level of the environment is above 45 dB, a volume gain of at least 20 dB above the ambient level shall be user selectable. A function shall be provided to automatically reset the volume to the default level after every use.	Not applicable	This product does not require or deliver voice output in a public area
(g) Color coding shall not be used as the only means of conveying information, indicating an action, prompting a response, or distinguishing a visual element.	This product uses text labels, symbols and/or icons to convey information	Color coding is not used as the sole means of conveying information on this printer



(h) When a product permits a user to adjust color and contrast settings, a range of color selections capable of producing a variety of contrast levels shall be provided.	Not applicable	This product does not permit a user to adjust the color or contrast setting on the LCD panel.
(i) Products shall be designed to avoid causing the screen to flicker with a frequency greater than 2 Hz and lower than 55 Hz.	Not applicable	This product does not have any screens that flicker or flash.
(j) (1) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: The position of any operable control shall be determined with respect to a vertical plane, which is 48 inches in length, centered on the operable control, and at the maximum protrusion of the product within the 48 inch length on products which are freestanding, non-portable, and intended to be used in one location and which have operable controls.	All operable controls on this Product are located within 24 inches of the front of the printer. There are indicator lights on the front panel of the printer which are visible from across the room.	This product is portable and may be easily moved from one location to another
(j)(2) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is 10 inches or less behind the reference plane, the height shall be 54 inches maximum and 15 inches minimum above the floor.	The operator panel on this Printer is on the front of the product and can be identified by touch. The printer is portable and can be placed at the convenience of the user. KMPS offers optional ADA-compliant printer stands which are designed to provide easier access for physically challenged users.	This product is portable and may be easily moved from one location to another for the convenience of the user.
(j)(3) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is more than 10 inches and not more than 24 inches behind the reference plane, the height shall be 46 inches maximum and 15 inches minimum above the floor.	The operator panel on this Printer is on the front of the product and can be identified by touch. All operable controls are located within 24 inches of the front of the printer. The printer is portable and can be placed at the convenience of the user.	This product is portable and may be easily moved from one location to another for the convenience of the user.
(j)(4) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Operable controls shall not be more than 24 inches behind the reference plane.	The operator panel on this Printer is on the front of the product and can be identified by touch. All operable controls are located within 24 inches of the front of the printer. The printer is portable and can be placed at the convenience of the user.	This product is portable and may be easily moved from one location to another for the convenience of the user.



magicolor 5430 DL

**SECTION 1194.25. SELF CONTAINED, CLOSED PRODUCTS
DETAIL VOLUNTARY PRODUCT ACCESSIBILITY TEMPLATE**

CRITERIA	SUPPORTING FEATURES	REMARKS AND EXPLANATIONS
(a) Self contained products shall be usable by people with disabilities without requiring an end-user to attach Assistive Technology to the product. Personal headsets for private listening are not Assistive Technology.	Color laser printer; up to 21 ppm monochrome and up to 21 ppm color; 2400 x 600 dpi resolution; memory 64 mb (standard)/512 mb (Max); The printer can be operated with one hand.	No Assistive Technology is required to use this Printer;
(b) When a timed response is required, the user shall be alerted and given sufficient time to indicate more time is required.	Any timed response associated with this printer provides at least two (2) minutes for the user to respond	Any timed response features associated with this printer give the user sufficient time to respond
(c) Where a product utilizes touchscreens or contact-sensitive controls, an input method shall be provided that complies with §1194.23 (k) (1) through (4).	This product does not utilize a touchscreen and any contact sensitive controls comply with § 1194.23 (k)(1) through (4)	This product does not utilize a touchscreen
(d) When biometric forms of user identification or control are used, an alternative form of identification or activation, which does not require the user to possess particular biological characteristics, shall also be provided.	Not applicable	This product does not utilize biometric controls
(e) When products provide auditory output, the audio signal shall be provided at a standard signal level through an industry standard connector that will allow for private listening. The product must provide the ability to interrupt, pause, and restart the audio at anytime.	Not applicable - This product does not provide auditory output as a standard feature.	This product does not provide auditory output as a standard feature
(f) When products deliver voice output in a public area, incremental volume control shall be provided with output amplification up to a level of at least 65 dB. Where the ambient noise level of the environment is above 45 dB, a volume gain of at least 20 dB above the ambient level shall be user selectable. A function shall be provided to automatically reset the volume to the default level after every use.	Not applicable	This product does not require or deliver voice output in a public area
(g) Color coding shall not be used as the only means of conveying information, indicating an action, prompting a response, or distinguishing a visual element.	This product uses text labels, symbols and/or icons to convey information	Color coding is not used as the sole means of conveying information on this printer



<p>(h) When a product permits a user to adjust color and contrast settings, a range of color selections capable of producing a variety of contrast levels shall be provided.</p>	<p>Not applicable</p>	<p>This product does not permit a user to adjust the color or contrast setting on the LCD panel.</p>
<p>(i) Products shall be designed to avoid causing the screen to flicker with a frequency greater than 2 Hz and lower than 55 Hz.</p>	<p>Not applicable</p>	<p>This product does not have any screens that flicker or flash.</p>
<p>(j) (1) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: The position of any operable control shall be determined with respect to a vertical plane, which is 48 inches in length, centered on the operable control, and at the maximum protrusion of the product within the 48 inch length on products which are freestanding, non-portable, and intended to be used in one location and which have operable controls.</p>	<p>All operable controls on this Product are located within 24 inches of the front of the printer. There are indicator lights on the front panel of the printer which are visible from across the room.</p>	<p>This product is portable and may be easily moved from one location to another</p>
<p>(j)(2) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is 10 inches or less behind the reference plane, the height shall be 54 inches maximum and 15 inches minimum above the floor.</p>	<p>The operator panel on this Printer is on the front of the product and can be identified by touch. The printer is portable and can be placed at the convenience of the user. KMPS offers optional ADA-compliant printer stands which are designed to provide easier access for physically challenged users.</p>	<p>This product is portable and may be easily moved from one location to another for the convenience of the user.</p>
<p>(j)(3) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is more than 10 inches and not more than 24 inches behind the reference plane, the height shall be 46 inches maximum and 15 inches minimum above the floor.</p>	<p>The operator panel on this Printer is on the front of the product and can be identified by touch. All operable controls are located within 24 inches of the front of the printer. The printer is portable and can be placed at the convenience of the user.</p>	<p>This product is portable and may be easily moved from one location to another for the convenience of the user.</p>
<p>(j)(4) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Operable controls shall not be more than 24 inches behind the reference plane.</p>	<p>The operator panel on this Printer is on the front of the product and can be identified by touch. All operable controls are located within 24 inches of the front of the printer. The printer is portable and can be placed at the convenience of the user.</p>	<p>This product is portable and may be easily moved from one location to another for the convenience of the user.</p>



magicolor 5440 DL

**SECTION 1194.25. SELF CONTAINED, CLOSED PRODUCTS
DETAIL VOLUNTARY PRODUCT ACCESSIBILITY TEMPLATE**

CRITERIA	SUPPORTING FEATURES	REMARKS AND EXPLANATIONS
(a) Self contained products shall be usable by people with disabilities without requiring an end-user to attach Assistive Technology to the product. Personal headsets for private listening are not Assistive Technology.	Color laser printer; up to 27 ppm monochrome and up to 27 ppm color; 2400 x 600 dpi resolution; memory 64 mb (standard)/512 mb (Max); The printer can be operated with one hand.	No Assistive Technology is required to use this Printer;
(b) When a timed response is required, the user shall be alerted and given sufficient time to indicate more time is required.	Any timed response associated with this printer provides at least two (2) minutes for the user to respond	Any timed response features associated with this printer give the user sufficient time to respond
(c) Where a product utilizes touchscreens or contact-sensitive controls, an input method shall be provided that complies with §1194.23 (k) (1) through (4).	This product does not utilize a touchscreen and any contact sensitive controls comply with § 1194.23 (k)(1) through (4)	This product does not utilize a touchscreen
(d) When biometric forms of user identification or control are used, an alternative form of identification or activation, which does not require the user to possess particular biological characteristics, shall also be provided.	Not applicable	This product does not utilize biometric controls
(e) When products provide auditory output, the audio signal shall be provided at a standard signal level through an industry standard connector that will allow for private listening. The product must provide the ability to interrupt, pause, and restart the audio at anytime.	Not applicable - This product does not provide auditory output as a standard feature.	This product does not provide auditory output as a standard feature
(f) When products deliver voice output in a public area, incremental volume control shall be provided with output amplification up to a level of at least 65 dB. Where the ambient noise level of the environment is above 45 dB, a volume gain of at least 20 dB above the ambient level shall be user selectable. A function shall be provided to automatically reset the volume to the default level after every use. (g) Color coding shall not be used as the only means of conveying information, indicating an action, prompting a response, or distinguishing a visual element.	Not applicable This product uses text labels, symbols and/or icons to convey information	This product does not require or deliver voice output in a public area Color coding is not used as the sole means of conveying information on this printer



(h) When a product permits a user to adjust color and contrast settings, a range of color selections capable of producing a variety of contrast levels shall be provided.	Not applicable	This product does not permit a user to adjust the color or contrast setting on the LCD panel.
(i) Products shall be designed to avoid causing the screen to flicker with a frequency greater than 2 Hz and lower than 55 Hz.	Not applicable	This product does not have any screens that flicker or flash.
(j) (1) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: The position of any operable control shall be determined with respect to a vertical plane, which is 48 inches in length, centered on the operable control, and at the maximum protrusion of the product within the 48 inch length on products which are freestanding, non-portable, and intended to be used in one location and which have operable controls.	All operable controls on this Product are located within 24 inches of the front of the printer. There are indicator lights on the front panel of the printer which are visible from across the room.	This product is portable and may be easily moved from one location to another
(j)(2) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is 10 inches or less behind the reference plane, the height shall be 54 inches maximum and 15 inches minimum above the floor.	The operator panel on this Printer is on the front of the product and can be identified by touch. The printer is portable and can be placed at the convenience of the user. KMPS offers optional ADA-compliant printer stands which are designed to provide easier access for physically challenged users.	This product is portable and may be easily moved from one location to another for the convenience of the user.
(j)(3) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is more than 10 inches and not more than 24 inches behind the reference plane, the height shall be 46 inches maximum and 15 inches minimum above the floor.	The operator panel on this Printer is on the front of the product and can be identified by touch. All operable controls are located within 24 inches of the front of the printer. The printer is portable and can be placed at the convenience of the user.	This product is portable and may be easily moved from one location to another for the convenience of the user.
(j)(4) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Operable controls shall not be more than 24 inches behind the reference plane.	The operator panel on this Printer is on the front of the product and can be identified by touch. All operable controls are located within 24 inches of the front of the printer. The printer is portable and can be placed at the convenience of the user.	This product is portable and may be easily moved from one location to another for the convenience of the user.

**magicolor 5450**SECTION 1194.25. SELF CONTAINED, CLOSED PRODUCTS
DETAIL VOLUNTARY PRODUCT ACCESSIBILITY TEMPLATE

CRITERIA	SUPPORTING FEATURES	REMARKS AND EXPLANATIONS
(a) Self contained products shall be usable by people with disabilities without requiring an end-user to attach Assistive Technology to the product. Personal headsets for private listening are not Assistive Technology.	Color laser printer; up to 27 ppm monochrome and up to 27 ppm color; 600 x 600 dpi resolution; memory 256 mb (standard)/1024 mb (Max); The printer can be operated with one hand.	No Assistive Technology is required to use this Printer;
(b) When a timed response is required, the user shall be alerted and given sufficient time to indicate more time is required.	Any timed response associated with this printer provides at least two (2) minutes for the user to respond	Any timed response features associated with this printer give the user sufficient time to respond
(c) Where a product utilizes touchscreens or contact-sensitive controls, an input method shall be provided that complies with §1194.23 (k) (1) through (4).	This product does not utilize a touchscreen and any contact sensitive controls comply with § 1194.23 (k)(1) through (4)	This product does not utilize a touchscreen
(d) When biometric forms of user identification or control are used, an alternative form of identification or activation, which does not require the user to possess particular biological characteristics, shall also be provided.	Not applicable	This product does not utilize biometric controls
(e) When products provide auditory output, the audio signal shall be provided at a standard signal level through an industry standard connector that will allow for private listening. The product must provide the ability to interrupt, pause, and restart the audio at anytime.	Not applicable - This product does not provide auditory output as a standard feature.	This product does not provide auditory output as a standard feature
(f) When products deliver voice output in a public area, incremental volume control shall be provided with output amplification up to a level of at least 65 dB. Where the ambient noise level of the environment is above 45 dB, a volume gain of at least 20 dB above the ambient level shall be user selectable. A function shall be provided to automatically reset the volume to the default level after every use.	Not applicable	This product does not require or deliver voice output in a public area
(g) Color coding shall not be used as the only means of conveying information, indicating an action, prompting a response, or distinguishing a visual element.	This product uses text labels, symbols and/or icons to convey information	Color coding is not used as the sole means of conveying information on this printer



(h) When a product permits a user to adjust color and contrast settings, a range of color selections capable of producing a variety of contrast levels shall be provided.	Not applicable	This product does not permit a user to adjust the color or contrast setting on the LCD panel.
(i) Products shall be designed to avoid causing the screen to flicker with a frequency greater than 2 Hz and lower than 55 Hz.	Not applicable	This product does not have any screens that flicker or flash.
(j) (1) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: The position of any operable control shall be determined with respect to a vertical plane, which is 48 inches in length, centered on the operable control, and at the maximum protrusion of the product within the 48 inch length on products which are freestanding, non-portable, and intended to be used in one location and which have operable controls.	All operable controls on this Product are located within 24 inches of the front of the printer. There are indicator lights on the front panel of the printer which are visible from across the room.	This product is portable and may be easily moved from one location to another
(j)(2) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is 10 inches or less behind the reference plane, the height shall be 54 inches maximum and 15 inches minimum above the floor.	The operator panel on this Printer is on the front of the product and can be identified by touch. The printer is portable and can be placed at the convenience of the user. KMPS offers optional ADA-compliant printer stands which are designed to provide easier access for physically challenged users.	This product is portable and may be easily moved from one location to another for the convenience of the user.
(j)(3) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is more than 10 inches and not more than 24 inches behind the reference plane, the height shall be 46 inches maximum and 15 inches minimum above the floor.	The operator panel on this Printer is on the front of the product and can be identified by touch. All operable controls are located within 24 inches of the front of the printer. The printer is portable and can be placed at the convenience of the user.	This product is portable and may be easily moved from one location to another for the convenience of the user.
(j)(4) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Operable controls shall not be more than 24 inches behind the reference plane.	The operator panel on this Printer is on the front of the product and can be identified by touch. All operable controls are located within 24 inches of the front of the printer. The printer is portable and can be placed at the convenience of the user.	This product is portable and may be easily moved from one location to another for the convenience of the user.



magicolor 3300

**SECTION 1194.25. SELF CONTAINED, CLOSED PRODUCTS
DETAIL VOLUNTARY PRODUCT ACCESSIBILITY TEMPLATE (VPAT)**

CRITERIA	SUPPORTING FEATURES	REMARKS AND EXPLANATIONS
(a) Self contained products shall be usable by people with disabilities without requiring an end-user to attach Assistive Technology to the product. Personal headsets for private listening are not Assistive Technology.	Color laser printer; up to 26 ppm monochrome and up to 26 ppm color; 1200 dpi resolution; memory 256 mb (standard)/512 mb (Max); The printer can be operated with one hand.	No Assistive Technology is required to use this Printer;
(b) When a timed response is required, the user shall be alerted and given sufficient time to indicate more time is required.	Any timed response associated with this printer provides at least two (2) minutes for the user to respond	Any timed response features associated with this printer give the user sufficient time to respond
(c) Where a product utilizes touchscreens or contact-sensitive controls, an input method shall be provided that complies with §1194.23 (k) (1) through (4).	This product does not utilize a touchscreen and any contact sensitive controls comply with § 1194.23 (k)(1) through (4)	This product does not utilize a touchscreen
(d) When biometric forms of user identification or control are used, an alternative form of identification or activation, which does not require the user to possess particular biological characteristics, shall also be provided.	Not applicable	This product does not utilize biometric controls
(e) When products provide auditory output, the audio signal shall be provided at a standard signal level through an industry standard connector that will allow for private listening. The product must provide the ability to interrupt, pause, and restart the audio at anytime.	Not applicable - This product does not provide auditory output as a standard feature. However, there is a Buzzbox™ available as an option that provides auditory and/or visual notification of any printer offline condition. Users with the Buzzbox™ can select a flashing light and/or beeping indicator to notify that the printer requires attention.	This product does not provide auditory output as a standard feature
(f) When products deliver voice output in a public area, incremental volume control shall be provided with output amplification up to a level of at least 65 dB. Where the ambient noise level of the environment is above 45 dB, a volume gain of at least 20 dB above the ambient level shall be user selectable. A function shall be provided to automatically reset the volume to the default level after every use.	Not applicable	This product does not require or deliver voice output in a public area



(g) Color coding shall not be used as the only means of conveying information, indicating an action, prompting a response, or distinguishing a visual element.	This product uses text labels, symbols and/or icons to convey information	Color coding is not used as the sole means of conveying information on this printer
(h) When a product permits a user to adjust color and contrast settings, a range of color selections capable of producing a variety of contrast levels shall be provided.	Not applicable	This product does not permit a user to adjust the color or contrast setting on the LCD panel.
(i) Products shall be designed to avoid causing the screen to flicker with a frequency greater than 2 Hz and lower than 55 Hz.	Not applicable	This product does not have any screens that flicker or flash.
(j) (1) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: The position of any operable control shall be determined with respect to a vertical plane, which is 48 inches in length, centered on the operable control, and at the maximum protrusion of the product within the 48 inch length on products which are freestanding, non-portable, and intended to be used in one location and which have operable controls.	All operable controls on this Product are located within 24 inches of the front of the printer. There are indicator lights on the front panel of the printer which are visible from across the room.	This product is portable and may be easily moved from one location to another
(j)(2) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is 10 inches or less behind the reference plane, the height shall be 54 inches maximum and 15 inches minimum above the floor.	The operator panel on this Printer is on the front of the product and can be identified by touch. The printer is portable and can be placed at the convenience of the user. KMPS offers optional ADA-compliant printer stands which are designed to provide easier access for physically challenged users.	This product is portable and may be easily moved from one location to another for the convenience of the user.
(j)(3) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is more than 10 inches and not more than 24 inches behind the reference plane, the height shall be 46 inches maximum and 15 inches minimum above the floor.	The operator panel on this Printer is on the front of the product and can be identified by touch. All operable controls are located within 24 inches of the front of the printer. The printer is portable and can be placed at the convenience of the user.	This product is portable and may be easily moved from one location to another for the convenience of the user.
(j)(4) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Operable controls shall not be more than 24 inches behind the reference plane.	The operator panel on this Printer is on the front of the product and can be identified by touch. All operable controls are located within 24 inches of the front of the printer. The printer is portable and can be placed at the convenience of the user.	This product is portable and may be easily moved from one location to another for the convenience of the user.



magicolor 7300

SECTION 1194.25. SELF CONTAINED, CLOSED PRODUCTS DETAIL VOLUNTARY PRODUCT ACCESSIBILITY TEMPLATE (VPAT)

CRITERIA	SUPPORTING FEATURES	REMARKS AND EXPLANATIONS
(a) Self contained products shall be usable by people with disabilities without requiring an end-user to attach Assistive Technology to the product. Personal headsets for private listening are not Assistive Technology.	Color laser printer; up to 20 ppm monochrome and up to 20 ppm color; 9600 x 600 dpi resolution; memory 256 mb (standard)/512 mb (Max); The printer can be operated with one hand.	No Assistive Technology is required to use this Printer;
(b) When a timed response is required, the user shall be alerted and given sufficient time to indicate more time is required.	Any timed response associated with this printer provides at least two (2) minutes for the user to respond	Any timed response features associated with this printer give the user sufficient time to respond
(c) Where a product utilizes touchscreens or contact-sensitive controls, an input method shall be provided that complies with §1194.23 (k) (1) through (4).	This product does not utilize a touchscreen and any contact sensitive controls comply with § 1194.23 (k)(1) through (4)	This product does not utilize a touchscreen
(d) When biometric forms of user identification or control are used, an alternative form of identification or activation, which does not require the user to possess particular biological characteristics, shall also be provided.	Not applicable	This product does not utilize biometric controls
(e) When products provide auditory output, the audio signal shall be provided at a standard signal level through an industry standard connector that will allow for private listening. The product must provide the ability to interrupt, pause, and restart the audio at anytime.	This product does provide auditory output in the form of a beep as a standard feature to notify the user of an offline condition. The beep is not the only form of notification of the off line condition. The signal is provided at a standard signal level. No other audio is provided as a standard feature. There is a Buzzbox™ available as an option that also provides auditory and/or visual notification of any printer offline condition. Users with the Buzzbox™ can select a flashing light and/or beeping indicator to notify that the printer requires attention.	This product does provide auditory output as a standard feature



(f) When products deliver voice output in a public area, incremental volume control shall be provided with output amplification up to a level of at least 65 dB. Where the ambient noise level of the environment is above 45 dB, a volume gain of at least 20 dB above the ambient level shall be user selectable. A function shall be provided to automatically reset the volume to the default level after every use.	Not applicable	This product does not require or deliver voice output in a public area
(g) Color coding shall not be used as the only means of conveying information, indicating an action, prompting a response, or distinguishing a visual element.	This product uses text labels, symbols and/or icons to convey information	Color coding is not used as the sole means of conveying information on this printer
(h) When a product permits a user to adjust color and contrast settings, a range of color selections capable of producing a variety of contrast levels shall be provided.	Not applicable	This product does not permit a user to adjust the color or contrast setting on the LCD panel.
(i) Products shall be designed to avoid causing the screen to flicker with a frequency greater than 2 Hz and lower than 55 Hz.	Not applicable	This product does not have any screens that flicker or flash.
(j) (1) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: The position of any operable control shall be determined with respect to a vertical plane, which is 48 inches in length, centered on the operable control, and at the maximum protrusion of the product within the 48 inch length on products which are freestanding, non-portable, and intended to be used in one location and which have operable controls.	All operable controls on this Product are located within 24 inches of the front of the printer. There are indicator lights on the front panel of the printer which are visible from across the room.	This product is portable and may be easily moved from one location to another
(j)(2) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is 10 inches or less behind the reference plane, the height shall be 54 inches maximum and 15 inches minimum above the floor.	The operator panel on this Printer is on the front of the product and can be identified by touch. The printer is portable and can be placed at the convenience of the user. KMPS offers optional ADA-compliant printer stands which are designed to provide easier access for physically challenged users.	This product is portable and may be easily moved from one location to another for the convenience of the user.
(j)(3) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is more than 10 inches and not more than 24 inches behind the	The operator panel on this Printer is on the front of the product and can be identified by touch. All operable controls are located within 24 inches of the front of the	This product is portable and may be easily moved from one location to another for the convenience of the user.



<p>reference plane, the height shall be 46 inches maximum and 15 inches minimum above the floor.</p>	<p>printer. The printer is portable and can be placed at the convenience of the user.</p>	
<p>(j)(4) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Operable controls shall not be more than 24 inches behind the reference plane.</p>	<p>The operator panel on this Printer is on the front of the product and can be identified by touch. All operable controls are located within 24 inches of the front of the printer. The printer is portable and can be placed at the convenience of the user.</p>	<p>This product is portable and may be easily moved from one location to another for the convenience of the user.</p>